



## CPC 4T Motorcycle Oil RW

- CPC 4T Motorcycle oil RW complies with the specifications of JASO MA and is specially designed for the lubrication of gasoline four-stroke motorcycle engine which requires JASO MA grade oils.
- The viscosity grade of the oil is SAE 30. The oil is manufactured with high performance base oils and new formulation technologies to be tied in the character of four-stroke motorcycle engine. It is suitable for highway and city driving mode.
- The oil is fully applicable to four-stroke engine motorcycles equipped with catalyst converter. It can offer four-stroke motorcycle engine wear reduction, contamination cleaning, and good lubrication.
- Package: 0.9 liter bottle, 0.9 liter\*12 case
- The typical data are listed as follow:

SAE Viscosity No.	30
Sp. Gr., 15.6°C/15.6°C, D4052	0.8906
Viscosity, Kin., cSt @40°C, D445	113.9
@100°C, D445	11.36
Viscosity Index, D2270	98
HTHS, cP ( $10^6 \text{ s}^{-1}$ ), D5481	3.55
Flash Point, COC, °C, D92	258
Fire Point, COC, °C, D92	293
Acid Number, mg KOH/g, D664	1.56
Base Number, mg KOH/g, D2896	5.28
Sulfated Ash, %c, D874	0.73
JASO Service Classification	MA
Product No.	LB52040

Note: Typical properties are based on standard tests under laboratory conditions. Variations that do not affect product performance are to be expected during normal manufacture. Please consult your local CPC representative if you have any questions.