



## CPC 9000 C3 Fully Synthetic Diesel Engine Oil

### 5W/30

- This oil meets the ACEA C3 and API SN/CF service grade by their specified testing institute and is also suitable for light duty diesel motor engine needs the oil of MB 229.51/229.31 、BMW Longlife-04 、VW 502.00/505.01 performance grade.
- The product is manufactured with the 100% fully synthetic base oil and the best additives. It gives excellent thermal stability 、viscosity retaining ability and seal compatibility. Its multi-grade viscosity of SAE 5W/30 is the best for highway and city driving mode.
- It is blended in new formulation which can offers light duty diesel motor engine more wear reduction 、engine cleaning and engine life prolongation with diesel particulate filter and three way catalyts.
- Packages: (1) 1 liter bottle, 1 liter\*12 case
- The typical test results are as follow:

SAE Viscosity No.	5W/30
Sp. Gr., 15.6°C/15.6°C, D4052	0.8490
Viscosity Kin., cSt@40°C, D445	68.7
@100°C, D445	11.6
Viscosity Index, D2270	164
HTHS, cP (10 <sup>6</sup> s <sup>-1</sup> ), D5481	3.54
Flash Point, COC, °C, D92	210
Fire Point, COC, °C, D92	242
Acid Number, mg KOH/g, D664	1.9
Base Number, mg KOH/g, D2896	7.9
ACEA Service Classification	C3
Product No.	LB51263

Note: Typical properties are based on standard tests under laboratory conditions. Variations that do not affect product performance are to be expected during normal manufacture. Please consult your local CPC representative if you have any questions.