



CPC Superfleet CG4 Motor Oil 15W/40

- CPC Superfleet CG4 Motor Oil is MTU Type 2 certified. The oil does not only meet the specifications of API CG4 but also the specifications of ACEA E3.
- The oil is manufactured from refined paraffinic base oils and formulated with the latest additives. It contains high performance additives, such as detergents, antioxidants, anti-wear, rust and corrosion inhibitors, anti-foam, etc. It does not only meet the specifications of API CG4 for bus/vans manufacturers in USA, Japan and other countries, but also meet the specifications of ACEA E3 for bus/vans manufacturers in European.
- The oil is widely used in various vehicles or engineering machinery with four-stroke diesel engines, and turbocharged and supercharged diesel engines.
- The oil is SAE 15W/40 oil and is used for all seasons
- Packages: (1) 200 liter drum
(2) 19 liter pail
(3) 18 liter pail
(3) 4 liter bottle, 4 liter*4 case
- The typical data are listed as follow:

SAE Viscosity No.	15W/40
Sp. Gr., 15.6°C/15.6°C, D4052	0.8745
Viscosity Kin., cSt @40°C	121.0
@100°C	15.70
Viscosity Index, D2270	137
Pour Point, °C, D6749	-30
Flash Point, COC, °C, D92	226
Fire Point, COC, °C, D92	248
Color, D1500	2.5
Base Number, mg KOH/g, D2896	8.9
Sulfated Ash, %, D874	1.0
API Service classification	CG4
Product No.	LB51940

Note: Typical properties are based on standard tests under laboratory conditions. Variations that do not affect product performance are to be expected during normal manufacture. Please consult your local CPC representative if you have any questions.