



CPC 4T Fully Synthetic Motorcycle Oil RT

- This Oil meets the standard of JASO service grades MA and API service grades SL by their specified testing institute.
- This Oil is a motorcycle engine oil, not only suitable for the past motorcycle engines which require SL grade oil but also the old model motorcycles which need SJ、SH grade oil.
- Manufactured with fully synthetic base oils, It gives excellent thermal stability、viscosity retaining ability and seal compatibility. Its multi-grade viscosity of SAE 10W/40 is the best for all seasons in Asia and suitable for highway and city driving mode. The draining mileage is much longer than conventional mineral oils.
- It is blended in new formulation which can offers motorcycle engine more wear reduction、engine cleaning and engine life prolongation with catalyst converter.
- Package: 0.9 liter bottle, 0.9 liter*12 case
- The typical test results are as follow:

SAE Viscosity No.	10W/40
Sp. Gr., 15.6°C/15.6°C, D4052	0.8585
Viscosity, Kin., cSt @40°C, D445	90.0
@100°C, D445	14.2
Viscosity Index, D2270	163
HTHS, cP (10 ⁶ s ⁻¹), D5481	3.9
Flash Point, COC, °C, D92	231
Fire Point, COC, °C, D92	250
Acid Number, mg KOH/g, D664	2.6
Base Number, mg KOH/g, D2896	6.3
Sulfated Ash, %, D874	0.68
JASO Service Classification	MA
API Service Classification	SL
Product No.	LB52041

Note: Typical properties are based on standard tests under laboratory conditions. Variations that do not affect product performance are to be expected during normal manufacture. Please consult your local CPC representative if you have any questions.