



## CPC 9000 SL Motor Oil 10W/40

- CPC 9000 SL Motor Oil 10W/40 is API SL certified.
- Adopting advanced fully synthetic formula technologies, the oil possesses strong oxidation stability, excellent detergency, and resistance to abrasion. It also provides the best lubrication and protection to the engine. The engine power output can last longer.
- The oil with multi-grade viscosity SAE 15W/40 is not only the best for all seasons and also takes the requirements of vehicle power transmission into account in both city and highway driving mode.
- The oil is recommended for gasoline engine vehicles which require API SL grade oil. It can fully replace the SJ, SH, SG or SF grade oils and provide better lubrication.
- The oil is fully applicable to the modern vehicles which are installed the catalytic converters.
- Package: 1 liter bottle, 1 liter\*12 case
- The typical data are listed as follow

SAE Viscosity No.	10W/40
Sp. Gr., 15.6°C/15.6°C, D4052	0.8585
Viscosity Kin., cSt@40°C, D445	93.4
@100°C, D445	14.21
Viscosity Index, D2270	157
HTHS, cP ( $10^6 \text{ s}^{-1}$ ), D5481	4.17
Pour Point, °C, D6749	-30
Flash Point, COC, °C, D92	224
Fire Point, COC, °C, D92	250
Base Number, mg KOH/g, D2896	6.34
API Service Classification	SL
Product No.	LB51311

Note: Typical properties are based on standard tests under laboratory conditions. Variations that do not affect product performance are to be expected during normal manufacture. Please consult your local CPC representative if you have any questions.