



## CPC Superfleet CK4 Motor Oil 15W/40

- CPC Superfleet CK4 Motor Oil 15W/40 is approved by the API Engine Oil Licensing & Certification System(EOLCS) and suitable for lubricating various heavy duty vehicles and engineering machinery with four stroke diesel engines.
- The oil meets the specifications of ACEA E7-16, E9-16 and JASO DH-2.
- The oil meets the European OEM specifications : MB228.31 、 MTU Type 2.1 、 MAN M3775 and Volvo VDS-4.5.
- The oil meets the American OEM specifications : Cummins CES 20086 、 Caterpillar ECF-3 and Ford WSS-M2C171-F1.
- The viscosity grade of this product is 15W/40 and it can be used in four seasons. CPC Superfleet CK-4 motor oil contains low sulfur base oils with high performance and modern formulation technology and it possesses excellent anti-oxidation and anti-wear ability.
- This oil is a low ash engine oil and suitable for modern diesel engines equipped with diesel particulate filter(DPF) and using diesel with sulfur content less than 15ppm. It meets the requirement of European Emission standards: Euro IV 、 V and VI and the specifications of European 、 American and Japan major heavy-duty vehicles manufacturers.
- Packages: (1) 200 liter drum  
(2) 19 liter pail
- The typical test results are as follows:

SAE Viscosity No.	15W/40
Sp. Gr., 15.6 o C/15.6 o C, D4052	0.8753
Viscosity Kin., cSt@40 °C, D445	112.6
@100 °C, D445	14.8
Viscosity Index, D2270	135
HTHS, cP (10 <sup>6</sup> s <sup>-1</sup> ), D5481	4.2
Flash Point, COC, °C, D92	224
Fire Point, COC, °C, D92	246
Pour Point, °C, D6749	-36
TBN, mg KOH/g, D2896	8.7
Sulfated Ash, wt%, D874	0.98
API Service Classification	CK4
Product No.	LB51290

Note: Typical properties are based on standard tests under laboratory conditions. Variations that do not affect product performance are to be expected during normal manufacture. Please consult your local CPC representative if you have any questions.