

## **CPC General Purpose Oil**

- CPC General Purpose Oils are highly refined pure mineral oils with excellent oxidation stability. The oils Possess very good ability for dissolving and flushing gum & sludge so that are also used in washing engine lubrication system.
- The oils are suited for the lubrication of gear box and bearing of general light duty work.
- CPC General purpose oil 50 is widely used in the lubrication of cylinder and bearing of burning-ball fishing boat engine.
- Packages: (1) in bulk
  - (2) 200 liter drum

71			
Grade No.	5(II)	10	20
Viscosity Grade	ISO VG 15	SAE 10	SAE 20
Sp. Gr., 15.6°C/15.6°C, D4052	0.8505	0.8674	0.8750
Viscosity, Kin., cSt@40°C, D445	13.43	26.26	46.03
@100°C,D445	3.12	4.83	6.891
Viscosity Index, D2270	88	105	103
Flash Point, COC, °C, D92	190	212	236
Pour Point, °C, D6749	-33	-12	-9
Color, D1500	L0.5	L0.5	0.5
Acid Number, mg KOH/g, D664	0.02	0.04	0.02
Product No.	LB51180	LB51161	LB51162

• The typical data are listed as follow:

Grade No.	30	40	50
Viscosity Grade	SAE 30	SAE 40	SAE 50
Sp. Gr., 15.6°C/15.6°C, D4052	0.8856	0.8883	0.8916
Viscosity, Kin., cSt@40°C,D445	97.28	135.6	205.8
@100°C,D445	10.92	13.86	18.21
Viscosity Index, D2270	96	98	97
Flash Point, COC, °C, D92	252	270	288
Pour Point, °C, D6749	-9	-9	-9
Color, D1500	L2.0	L2.0	L3.0
Acid Number, mg KOH/g, D664	0.05	0.06	0.04
Product No.	LB51163	LB51164	LB51165

Note: Typical properties are based on standard tests under laboratory conditions. Variations that do not affect product performance are to be expected during normal manufacture. Please consult your local CPC representative if you have any questions.