



CPC Way Lubricant

- CPC Machine Way Lubricant is especially refined and added special additives with excellent metal surface adhesion that can lubricate folding-face and bed-stage way of various heavy duty machine to avoid or reduce bed-stage stick-slip and promote the quality of processed products.
- The oils meet the machine way specifications of American Cincinnati Milacron P-47 and become the one of the company approved products.
- Packages: (1) 200 liter drum
(2) 19 liter pail (for 32 and 68)
- The typical data are listed as follow:

Grade No.	32	68	150	220
Viscosity Grade, ISO VG	32	68	150	220
Sp. Gr., 15.6°C/15.6°C, D4052	0.8723	0.8855	0.8922	0.8953
Viscosity, Kin., cSt @ 40°C, D445	33.3	68.4	141.9	234.2
@ 100°C, D445	5.57	8.82	14.27	19.67
Viscosity Index, D2270	104	101	98	96
Pour Point, °C, D6749	-12	-12	-12	-12
Flash Point, COC, °C, D92	218	218	230	242
Color, D1500	3.0	3.0	L4.0	L4.0
Acid Number, mg KOH/g, D664	1.66	1.51	1.70	1.61
Product No.	LA81032	LA81068	LA81150	LA81220

Note: Typical properties are based on standard tests under laboratory conditions. Variations that do not affect product performance are to be expected during normal manufacture. Please consult your local CPC representative if you have any questions.