



## CPC All Purpose Oil

- CPC All Purpose Oils are very high degree of refining lubricants. The oils have a unique combination of properties: light color, good oxidation stability, low pour point, and low carbon residue. Widely apply to the following parts:
  - (1) Lubrication of air compressors, vacuum pump cylinders, and bearings.
  - (2) Lubrication of freezer cylinders and crankshafts.
  - (3) Lubrication of low temperature hydraulic systems.
- Package: 200 liter drum
- The typical data are listed as follow:

Grade No.	46	68
Viscosity Grade, ISO VG	46	68
Sp. Gr., 15.6°C/15.6°C, D4052	0.9034	0.9060
Viscosity, Kin., cSt @40°C, D445	46.82	64.08
@100°C, D445	5.94	7.12
Viscosity Index, D2270	52	54
Pour Point, °C, D6749	-39	-30
Flash Point, COC, °C, D92	180	202
Color, D1500	L0.5	L0.5
Acid Number, mg KOH/g, D664	0.02	0.04
Carbon Residue, Rams., %, D524	0.08	0.08
Product No.	LA64531	LA64532

Note: Typical properties are based on standard tests under laboratory conditions. Variations that do not affect product performance are to be expected during normal manufacture. Please consult your local CPC representative if you have any questions.