Safety Data Sheet

No: L133 CPC Circulation Oil HP15 Ver. 1.0

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: CPC Circulation Oil HP15

Product Code: LA60915

Manufacturer Name: Lubricants Business Division, CPC Corporation, Taiwan

Address:

6F, 15, Cheng-Kung 2nd RD, Chen-Zerng District, Kaohsiung, 806, Taiwan, R.O.C.

Telephone Number: 886-7-5361510

Emergency Telephone Number: 886-5-2224171 Ext. 7250 or 6666

Fax Number: 886-5-2232062

II. HAZARDS IDENTIFICATION

The Most Important Hazardous Effects:

1. Adverse Human Health Effects: (For Long Term Exposure)

• Eye Contact: irritation.

• Skin Contact: may cause dermatitis.

- Inhalation: inhalation of oil mist or vapors at elevated temperature may cause respiratory irritation.
- Ingestion: no information is available.
- **2. Environmental Effects:** no information is available.
- 3. Physical and Chemical Hazards: Mist or vapors can produce at elevated temperatures.
- 4. Specific Hazards: no information on significant adverse effects.

Main Symptoms:

• Eye Contact: irritation.

• Skin Contact: no information is available.

• Inhalation: no information on significant adverse effects.

• Ingestion: no information is available.

NFPA Ratings (Scale 0-4): Health=1 Fire=1 Reactivity=0

III. COMPOSITION, INFORMATION ON INGREDIENT

1. Product Identification:

Chemical Family: Petroleum Hydrocarbons

Chemical Formula: Mixture

Trade Name/Synonym: Not assigned

2. Component:

Ingredients	CAS Number	% by wt.
Light Paraffinic Distillate	64742-55-8	>90
Additives		<10

IV. FIRST AID MEASURE

Emergency Procedures:

• Inhalation:

Remove personnel from exposure area to fresh air immediately. If breathing is difficult, give oxygen. If breathing ceases, use a oxygen rescuer or similar device to perform artificial respiration. Get medical attention immediately.

• Skin Contact:

Remove contaminated clothing, jewelry and shoes immediately. Wash with soap or mild detergent and large amounts of water until no evidence of chemical remains (at least $15 \sim 20$ minutes). If irritation or adverse symptoms develop, seek medical attention.

• Eye Contact:

Flush eyes immediately with running water for at least fifteen minutes, occasionally lifting upper and lower lids, until no evidence of chemical remains. Get medical attention immediately.

• Digestion:

If vomiting occurs, keep head lower than hips to help prevent aspiration. Get medical attention.

Protection of First-aider: no information is available.

Notes to Physician: no information is available.

V. FIRE FIGHTING MEASURES

Suitable Extinguishing Media: regular dry chemical, carbon dioxide, water, regular Foam. Large fires: Use regular foam or flood with fine water spray.

Specific Hazards: Incomplete burning can produce carbon monoxide and/or carbon dioxide and other harmful products.

Special Fire Fighting Procedures:

- 1. Firefighters should wear proper protective equipment stay upwind.
- 2. Move container from fire area and shut off source if it can be done without risk.
- 3. Cool containers with water spray until well after the fire is out.
- 4. Do not scatter spilled material with high-pressure water streams.
- 5. Keep unnecessary people away, isolate hazard area and deny entry.
- 6. Avoid inhalation of material or combustion by-products.

VI. ACCIDENTAL RELEASE MEASURES

Personal Precautions:

- 1. Avoid heat, flames, sparks and other sources of ignition.
- 2. Stop leak if possible without personal risk.
- 3. Reduce vapors with water spray.

Environmental Precautions:

- 1. Eliminate all open flame in vicinity of spill or released vapor.
- 2. Stop the source of the leak or release.
- 3. Clean up releases as soon as possible.
- 4. Contain liquid to prevent further contamination of soil, surface water or groundwater.

Methods for Cleaning Up:

- 1. Clean up small spills using sand or other non-combustible material.
- 2. Collect spilled material in appropriate container for disposal.
- 3. Where feasible and appropriate, remove contaminated soil.
- 4. Follow prescribed procedures for reporting and responding to larger releases.

VII. HANDLING AND STORAGE

Handling:

- 1. Wear protective equipment, if exposure conditions warrant.
- 2. Wash thoroughly after handling.
- 3. Use with adequate ventilation.

4. Handle in accordance with all current regulations and standards.

Storage:

- 1. Keep away from heat, sparks and flames.
- 2. Store in well-ventilated area.
- 3. Store in a tightly closed container.
- 4. Store in a cool, dry place.
- 5. Bond and ground during transfer.
- 6. Keep separated from incompatible substances.
- 7. Storage in accordance with all current regulations and standards.

VIII. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Engineering Control:

Provide local exhaust ventilation system. Ensure compliance with applicable exposure limits.

Control Parameter:

HAZARDOUS MATERIAL	TWA	STEL	CEILING
Mineral Oil Mist	ACGIH: 5 mg/m ³ NIOSH: 5 mg/m ³ OSHA: 5 mg/m ³	NIOSH: 10mg/m³ UK OES: 10mg/m³	

Personal Protection Equipment:

• Respiratory Protection:

Not generally required unless needed to prevent respiratory irritation. In case of spill or leak resulting in unknown concentration, use NOISH approved supplied air respirator.

• Hand Protection:

Wear appropriate chemical resistant gloves.

• Eye Protection:

Wear splash resistant safety goggles or face shield. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

• Skin and Body Protection:

Wear appropriate chemical resistant clothing. Remove any chemical soaked clothing immediately.

IX. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: liquid	Form:Yellow brown viscous liquid
1	*

Color: Yellow brown	Odor no specific irritant odor	
PH : Not available	Boiling Point/Range: No data	
Decomposition Temperature: No data	Flash Point: 192°C Test Method: Open Cup	
Autoignition Temperature: No data	Flammable Limits: Not available	
Vapor Pressure: Not available	Vapor Density: Not available	
Specific Gravity: 0.87 g/cm³ @ 15.6°C	Solubility: Insoluble in water	

X. STABILITY AND REACTIVITY

Stability: Stable at normal temperatures and pressure.

Possible Hazardous Reactions: Will not polymerize.

Conditions to Avoid:

Avoid extreme heat. Avoid contact with incompatible material.

Materials to Avoid: acid. strong oxidizing agents.

Hazardous Decomposition Products:

oxides of carbon, various hydrocarbons formed when burned.

XI. TOXICOLOGICAL INFORMATION

Acute Toxicity:

- Inhalation: Mists or sprays of insoluble oils are not harmful to the respiratory tract, although worker discomfort may occur at oil mist level of 5 mg/m³.
- Skin Contact: May cause hair follicles, comedones, perifollicular papules and pustules. Some individuals may develop a skin sensitivity to petroleum products.
- Eye Contact: Found to be moderately irritating to rabbit eyes.
- Ingestion: Mineral oils may cause gastrointestinal disturblance such as diarrhea.

Local Effect: No data available.

Sensitization: No data available.

Chronic Toxicity:

- Inhalation: Repeated or prolonged contact with oils may cause fibrotic nodules, lipoid pneumonia, and lipid granuloma.
- Skin Contact: Repeated or prolonged contact may cause defatting of the skin which may result in dermatitis and effect as detailed in acute exposure.
- Eye Contact: Repeated or prolonged contact with irritants may cause conjunctivitis.
- Ingestion: No data available.

Specific Effects: No data available.

XII. ECOLOGICAL INFORMATION

Environmental Mobility: Fates: This material is not expected to present any environmental problems other than those associated with oil spills.

XIII. DISPOSAL CONSIDERATIONS

Subject to disposal regulations:

Dispose in accordance with all applicable regulations.

XIV. TRANSPORT INFORMATION

This product is not classified as dangerous for this mode (IATA) of transport. Therefore 14.1 UN Nunber, 14.2 UN Proper Shipping name, 14.3 Transport hazard class, 14.4 Packing group, 14.5 Environmental hazards, 14.6 Special precautions for user do not apply.

XV. REGULATORY INFORMATION

Suitable Regulations:

1. U.S. Regulations:

TSCA Inventory Status: Y

SARA Hazard Categories, SARA Sections 311/312 (40 CFR 370.21)

Acute: N Chronic: N Fire: N Reactive: N

OSHA Process Safety (29 CFR 1910.119):N

2. State Regulations:

California Proposition 65: N

3.	European Regulations: EC Number: Not assigned
----	---

XVI. OTHER INFORMATION

Reference Literatures	OHS 15037	
	OHS 50237	
	SDS of Additives	
Made By	Lubricants Business Division, CPC Corporation, Taiwan	
	Title: OHS Manager	Name : Fong-Wu Chen
Creation Date	July 11, 2019	

CPC Corporation, Taiwan (CPC) believes that the information contained herein (including data and statements) is accurate as of the date hereof.

NO ANY WARRANTY, EXPRESS OR IMPLIED, IS MADE AS CONCERNS THE INFORMATION HEREIN PROVIDED.

The information provided herein relates only to the specific product designated and may not be valid where such product is used in combination with any other materials or in any process. Further, since the conditions and methods of use of the product and information referred to herein which are beyond the control of CPC.

CPC expressly disclaims any and all liability as to any results obtained or arising from any use of product or such information.