

Safety Data Sheet

No : L212 CPC Extended-Life Screw Compressor Oil Ver. 2.0

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: CPC Extended-Life Screw Compressor Oil

Product Code: . LA-69346

Manufacturer Name: CPC Corporation Taiwan, Lube Business Division.

Address:

6F, 15, Cheng-Kung 2nd RD, Chen-Zerng District, Kaohsiung, 806,Taiwan, R.O.C.

Telephone Number: 886-7-5361510

Emergency Telephone Number: 886-5-2224171 Ext. 7250

Fax Number: 886-5-2232062

II. HAZARDS IDENTIFICATION

The Most Important Hazardous Effects:

1. Adverse Human Health Effects:

(For Long Term Exposure)

- Inhalation: inhalation of oil mist or vapors at elevated temperature may cause respiratory irritation.
- Skin Contact : skin disorders.
- Eye Contact : irritation.
- Ingestion: no information is available.

2. Environmental Effects: no information is available.

3. Physical and Chemical Hazards: Mist or vapors can produce at elevated temperatures.

4. Specific Hazards: no information on significant adverse effects.

Precautionary Statements-Prevention:

- 1.Keep away from heat, sparks, flames and hot surfaces — No Smoking.
- 2.Wear protective gloves and clothing. Wear eye protection and face protection.
- 3.Store in a well-ventilated place. — Keep Cool.

NFPA Ratings (Scale 0-4): Health=1 Fire=1 Reactivity=0

III. COMPOSITION, INFORMATION ON INGREDIENTS

1. Product Identification:		
Chemical Family: Petroleum Hydrocarbons		
Chemical Formula: Mixture		
Trade Name/Synonym: Not assigned		
2. Component:		
Ingredients	% by wt.	
Hydrotreated Heavy Paraffinic Oil	90-95	(NFPA FIRE = 1)
Polyalkylene glycol	5-10	(NFPA FIRE = 1)
Additives	1-5	(NFPA FIRE = 1)

IV. FIRST AID MEASURES

Emergency Procedures:
<ul style="list-style-type: none"> • Inhalation : Remove personnel from exposure area to fresh air immediately. If breathing is difficult, give oxygen. If breathing ceases, use a oxygen rescuer or similar device to perform artificial respiration. Get medical attention immediately. • Skin Contact : Remove contaminated clothing, jewelry and shoes immediately. Wash with soap or mild detergent and large amounts of water until no evidence of chemical remains (at least 15 ~ 20 minutes). If irritation or adverse symptoms develop, seek medical attention. • Eye Contact : Flush eyes immediately with running water for at least fifteen minutes, occasionally lifting upper and lower lids, until no evidence of chemical remains. Get medical attention immediately. • Digestion : If vomiting occurs, keep head lower than hips to help prevent aspiration. Get medical attention.

Protection of First-aider: no information is available.

Notes to Physician: no information is available.

V. FIRE FIGHTING MEASURES

Suitable Extinguishing Media: Regular dry chemical, carbon dioxide, water, regular foam.
Large fires: Use regular foam or flood with fine water spray.

Specific Hazards: Incomplete burning can produce carbon monoxide and/or carbon dioxide and other harmful products.

Special Fire Fighting Procedures:

1. Firefighters should wear proper protective equipment stay upwind.
2. Move container from fire area and shut off source if it can be done without risk.
3. Cool containers with water spray until well after the fire is out.
4. Do not scatter spilled material with high-pressure water streams.
5. Keep unnecessary people away, isolate hazard area and deny entry.
6. Avoid inhalation of material or combustion by-products.

VI. ACCIDENTAL RELEASE MEASURES

Personal Precautions:

1. Avoid heat, flames, sparks and other sources of ignition.
2. Stop leak if possible without personal risk.
3. Reduce vapors with water spray.

Environmental Precautions:

1. Eliminate all open flame in vicinity of spill or released vapor.
2. Stop the source of the leak or release.
3. Clean up releases as soon as possible.
4. Contain liquid to prevent further contamination of soil, surface water or groundwater.

Methods for Cleaning Up:

1. Clean up small spills using sand or other non-combustible material.
2. Collect spilled material in appropriate container for disposal.
3. Where feasible and appropriate, remove contaminated soil.
4. Follow prescribed procedures for reporting and responding to larger releases.

VII. HANDLING AND STORAGE

Handling:

1. Wear protective equipment, if exposure conditions warrant.
2. Wash thoroughly after handling.
3. Use with adequate ventilation.
4. Handle in accordance with all current regulations and standards.

Storage:

1. Keep away from heat, sparks and flames.
2. Store in well-ventilated area.
3. Store in a tightly closed container.
4. Store in a cool, dry place.
5. Bond and ground during transfer.
6. Keep separated from incompatible substances.
7. Storage in accordance with all current regulations and standards.

VIII. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Engineering Control:

Provide local exhaust ventilation system. Ensure compliance with applicable exposure limits.

Control Parameter:

HAZARDOUS MATERIAL	TWA	STEL	CEILING
Mineral Oil Mist	ACGIH: 5 mg/m ³ NIOSH: 5 mg/m ³ OSHA : 5 mg/m ³	NIOSH : 10mg/m ³ UK OES : 10mg/m ³	--

Personal Protection Equipment:

- Respiratory Protection:
Not generally required unless needed to prevent respiratory irritation. In case of spill or leak resulting in unknown concentration, use NOISH approved supplied air respirator.
- Hand Protection:
Wear appropriate chemical resistant gloves.
- Eye Protection:
Wear splash resistant safety goggles or face shield. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.
- Skin and Body Protection:
Wear appropriate chemical resistant clothing. Remove any chemical soaked clothing immediately.

IX. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: liquid	Form: light amber liquid
Color: Brown	Odor: a little waxy odor
pH: Not available	Boiling Range: No data
Decomposition Temperature: No data	Flash Point: 244°C (COC) Test Method: Open Cup
Autoignition Temperature: No data	Flammable Limits: Not available
Vapor Pressure: Not available	Vapor Density: Not available
Specific Gravity: 0.8511g/cm ³ @ 60°F	Solubility: insoluble in water
Flammability(solid, gas): Not available	Evaporation rate: No data
n-Octanol/water, Partition coefficient: No data	Melting/Freezing point: No data

X. STABILITY AND REACTIVITY

Stability: Stable at normal temperatures and pressure.

Possible Hazardous Reactions: Will not polymerize.

Conditions to Avoid:

Avoid heat, flames, spark and other sources of ignition. Avoid contact within compatible material.

Materials to Avoid: strong oxidizing agents.

Hazardous Decomposition Products:

oxides of carbon and various hydrocarbons formed when burned.

XI. TOXICOLOGICAL INFORMATION

Acute Toxicity:

- Inhalation:
Mists or sprays of insoluble oils are not harmful to the respiratory tract, although worker discomfort may occur at oil mist level of 5 mg/m^3 .
- Skin Contact:
May cause hair follicles, comedones, perifollicular papules and pustules. Some individuals may develop a skin sensitivity to petroleum products.
- Eye Contact:
Found to be moderately irritating to rabbit eyes.
- Ingestion:
Mineral oils may cause gastrointestinal disturbance such as diarrhea.

Local Effect: No data available.

Sensitization: No data available.

Chronic Toxicity:

- Inhalation:
Repeated or prolonged contact with oils may cause fibrotic nodules, lipoid pneumonia, and lipid granuloma.
- Skin Contact:
Repeated or prolonged contact may cause defatting of the skin which may result in dermatitis and effect as detailed in acute exposure.
- Eye Contact: Repeated or prolonged contact with irritants may cause conjunctivitis.
- Ingestion: No data available.

Specific Effects: No data available.

XII. ECOLOGICAL INFORMATION

- Ecotoxicity: No special environmental measures are necessary.
- Persistence and degradability: The product is not readily biodegradable, but it can be degraded by micro-organisms, it is regarded as being inherently biodegradable.
- Bioaccumulation: No information available.
- Mobility: The product is insoluble and floats on water, is not likely mobile in the environment due its low water solubility.
- Other adverse effects: No information available.

XIII. DISPOSAL CONSIDERATIONS

Subject to disposal regulations:

Dispose in accordance with all applicable regulations.

- Waste treatment methods: Dispose of in accordance with local and national regulations.
- Contaminated packaging: Observe all label precautions until container is cleaned, reconditioned or destroyed. Empty containers should be taken to an approved waste handling site for recycling or disposal.

XIV. TRANSPORT INFORMATION

No classification assigned.

XV. REGULATORY INFORMATION

Suitable Regulations:

1. U.S. Regulations:

TSCA Inventory Status: Y

SARA Hazard Categories, SARA Sections 311/312(40 CFR 370.21):

Acute: N

Chronic: N

Fire: N

Reactive: N

OSHA Process Safety(29 CFR 1910.119): N

2. State Regulations:

California Proposition 65: N

3. European Regulations:
EC Number: Not assigned

XVI. OTHER INFORMATION

Reference Literatures	1. OHS11250 2. SDS of Additives	
Made by	CPC Corporation Taiwan, Lube Business Division	
	Address/Telephone: 217,Min Sheng S.Road, Chia-Yi, Taiwan. 60051, R.O.C / 886-5-2224171 ext.7250	
	Title: OHS manager	Name: Fong-wu CHEN
Creation Date	Jan. 06, 2022	

CPC Corporation Taiwan believes that the information contained herein (including data and statements) is accurate as of the date hereof.

NO ANY WARRANTY, EXPRESS OR IMPLIED, IS MADE AS CONCERNS THE INFORMATION HEREIN PROVIDED.

The information provided herein relates only to the specific product designated and may not be valid where such product is used in combination with any other materials or in any process. Further, since the conditions and methods of use of the product and information referred to herein are beyond the control of CPC Taiwan.

CPC Taiwan expressly disclaims any and all liability as to any results obtained or arising from any use of product or such information.