

CPC Marilube Oil SL-30, SL-40

- CPC Marilube Oil SL-30, SL-40 are high quality internal combustion engine lubricants specially designed for the lubrication of medium speed trunk-type diesel engines that run on heavy oils or high sulfur residual fuels.
- The oils contain the excellent properties of detergent and dispersant which can assure engine cylinders and pistons clean and lighter carbon deposits.
- The oils possess the excellent performances of high-temperature thermal oxidation stability, anti-wear, and anti-rust which can effectively lubricate the cylinders.
- Their high TBN, around 40 mg KOH/g, can efficiently neutralize acid sulfides which come from burning heavy oils or fuels, and thereby reduce the corrosive wear of the cylinder inner wall and the bearings.
- Packages: (1) in bulk

(2) 200 liter drum

■ The typical data are listed as follow:

Grade No.	SL-30	SL-40
SAE Viscosity No.	30	40
Sp. Gr., 15.6°C/15.6°C, D4052	0.9066	0.9124
Viscosity, Kin., cSt @40°C, D445	101.0	145.1
@100°C,D445	11.70	15.0
Viscosity Index, D2270	104	104
Pour Point °C, D6749	-9	-9
Flash Point, COC, °C, D92	254	258
Base Number, mg KOH/g, D2896	41.66	41.73
Product No.	LB54303	LB54304

Note: Typical properties are based on standard tests under laboratory conditions. Variations that do not affect product performance are to be expected during normal manufacture. Please consult your local CPC representative if you have any questions.