



CPC Auto Grease

- The property and application of CPC Auto Grease is the same as CPC Multi-Purpose Grease NLGL No.2. It is dubbed "Auto" for being used in vehicles widely.
- The grease is recommended for the wheel bearings, water pumps, chassis, universal joints, springs, etc. of all kinds vehicles and develops excellent lubricating performances.
- CPC Multi-Purpose Grease No.3 can also be introduced to where thicker grease to be needed in some heavy-weighted vehicles.
- Packages: (1) 180 kg drum
(2) 15 kg pail
(3) 0.5 kg can, 0.5 kg*24 case
- The typical data are listed as follow:

NLGI ASTM Type	No.2
Dropping Point, °C, D2265	209
Penetration, D217	
60worked, 1/10mm	274
10,000worked, 1/10mm	282
Color, Visual	Amber
Oxidation Stability, D942	
100hrs, Pressure Drop, psi	4.0
500hrs, Pressure Drop, psi	9.0
Anti-Rust Test, D1743	Pass
Soap Base	Lithium
Roll Test, %, D1831	5.1
Water Washout, 79°C, %, D1264	2.5
Wheel Bearing Leakage Test, g, D1263	2.3
Viscosity of Mineral Oil, cSt ,@100°C, D445	19.02
Product No.	LB80102

Note: Typical properties are based on standard tests under laboratory conditions. Variations that do not affect product performance are to be expected during normal manufacture. Please consult your local CPC representative if you have any questions.