

CPC High Adhesive Grease No.0

- CPC High Adhesive Grease No.0 is made from high quality base oils and special additives to provide strong surface adhesion, high fluidity, and excellent load-carrying ability. It also possesses good oxidation stability, anti-rust property, and mechanical stability.
- The grease's consistency NLGI grade is No.0 and it is suitable for lubrication of small-sized gear reducers. In dynamic applications, strong adhesion of the grease provides good lubrication. In static uses, it is suitable for automatic greasing and has effects of lubrication and sealing.
- Avoid mixing with other brands of grease when in use. Make sure to clean used greases with other brands thoroughly before filling CPC High Adhesive Grease No.0.
- Packages: (1) 170 kg drum
 - (2) 15 kg pail
- The typical data are listed as following:

	
NLGI Grade No.	No.0
Dropping Point, °C, D2265	>300
Penetration, D217	
60worked, 1/10mm	373
10,000worked, 1/10mm	389
Color, Visual	Amber
Oxidation Stability, D942	
100hrs, Pressure Drop, psi	4.3
500hrs, Pressure Drop, psi	11.5
Copper Corrosion, 100°C, 24hrs, D4048	1a
Soap Base	Lithium Complex
Timken E.P., OK Load, Lbs., D2509	40
Product No.	LB82000

Note: Typical properties are based on standard tests under laboratory conditions. Variations that do not affect product performance are to be expected during normal manufacture. Please consult your local CPC representative if you have any questions.