

MiRAGE APEX SJ 20W/50 4T Motor Oil

- This oil is suitable for 4T motorcycle engine need the lubricant of the API SJ service grade and the JASO MA service grade by their specified testing institute.
- This oil is a 4T motorcycle engine oil, not only suitable for the past motorcycle engines which require API SH grade oil but also the old model motorcycles which need API SH · SG grade oil.
- The product is manufactured with the good base oil and additives. It gives excellent thermal stability · viscosity retaining ability and seal compatibility. Its multi-grade viscosity of SAE 20W/50 is the best for highway and city driving mode.
- It is blended in new formulation which can offers motorcycle engine more wear reduction · engine cleaning and engine life prolongation with catalyst converter.
- Package: (1) 1 liter bottle, 1 liter*12 case.
 (2) 0.85 liter bottle, 0.85 liter*12 case.
 (3) 0.8 liter bottle, 0.8 liter*12 case.
 (4) 0.7 liter bottle, 0.7 liter*12 case.
- The typical test results are as follow:

SAE Viscosity No.	20W/50
Sp., 15.6°C/15.6°C	0.887
Viscosity Kin., cSt@40°C, D445	157.8
@ 100°C, D445	18.12
Viscosity Index, D2270	127
HTHS, cP (10 ⁶ s ⁻¹), D5481	4.73
Pour Point, °C, D6749	-30
Flash Point, COC, °C, D92	245
Fire Point, COC, °C, D92	260
Acid Number, mg KOH/g, D664	2.4
Base Number, mg KOH/g, D2896	7.5
JASO Service Classification	MA
API Service Classification	SJ
Product No.	LM51325

Note: Typical properties are based on standard tests under laboratory conditions. Variations that do not affect product performance are to be expected during normal manufacture. Please consult your local CPC representative if you have any questions.