

MiRAGE APEX SN 5W/30 合成 4T 機車專用油

- This oil is suitable for 4T motorcycle engine need the lubricant of the API SN service grade and the JASO MA service grade by their specified testing institute.
- This oil is a 4T motorcycle engine oil, not only suitable for the past motorcycle engines which require API SN grade oil but also the old model motorcycles which need API SM、SL grade oil.
- The product is manufactured with the synthetic base oil and new additives. It gives excellent thermal stability viscosity retaining ability and seal compatibility. Its multigrade viscosity of SAE 5W/30 is the best for city driving mode.
- It is blended in new lower Phosphors additives formulation which can offers motorcycle engine more wear reduction · engine cleaning and engine life prolongation with catalyst converter.
- Package: (1) 1 liter bottle, 1 liter*12 case. (2) 0.8 liter bottle, 0.8 liter*12 case.
- The typical test results are as follow:

SAE Viscosity No.	5W/30
Sp. Gr., 15.6°C/15.6°C, D4052	0.8547
Viscosity Kin., cSt@40°C, D445	63.23
@100°C, D445	10.51
Viscosity Index, D2270	156
HTHS, $cP(10^6 s^{-1})$, D5481	3.1
Flash Point, COC, °C, D92	220
Fire Point, COC, °C, D92	242
Acid Number, mg KOH/g, D664	2.3
Base Number, mg KOH/g, D2896	7.6
JASO Service Classification	MA
API Service Classification	SN
Product No.	LM51383

Note: Typical properties are based on standard tests under laboratory conditions. Variations that do not affect product performance are to be expected during normal manufacture. Please consult your local CPC representative if you have any questions.