



MiRAGE APEX SM 10W/40 Synthetic 4T Motor Oil

- This oil is suitable for 4T motorcycle dry clutch engine needs the lubricant of the API SM service grade by their specified testing institute. The oil can not be used in 4T motorcycle wet clutch engine to avoid hurting the clutch/gear parts and abnormal transmission.
- The product is manufactured with the synthetic base oil and new additives. It gives excellent thermal stability、viscosity retaining ability and seal compatibility. Its multi-grade viscosity of SAE 10W/40 is the best for highway and city driving mode.
- It is blended in new lower Phosphors additives formulation which can offers motorcycle engine more wear reduction、engine cleaning and engine life prolongation with catalyst converter.
- Package: 1 liter bottle, 1 liter*12 case.
- The typical test results are as follow:

SAE Viscosity No.	10W/40
Sp., 15.6°C/15.6°C	0.8585
Viscosity Kin., cSt@40 °C, D445	103.6
@100 °C, D445	15.1
Viscosity Index, D2270	153
HTHS, cP (10 ⁶ s ⁻¹), D5481	4.17
Flash Point, COC, °C, D92	224
Fire Point, COC, °C, D92	250
Acid Number, mg KOH/g, D664	1.7
Base Number, mg KOH/g, D2896	6.3
JASO Service Classification	SM
API Service Classification	LM51372

Note: Typical properties are based on standard tests under laboratory conditions. Variations that do not affect product performance are to be expected during normal manufacture. Please consult your local CPC representative if you have any questions.