

## MiRAGE APEX SM 10W/40 4T Motorcycle Oil

- This oil is suitable for 4T motorcycle engine need the lubricant of the API SM service grade and the JASO MA service grade by their specified testing institute.
- This oil is a 4T motorcycle engine oil, not only suitable for the past motorcycle engines which require API SL grade oil but also the old model motorcycles which need API SJ 、SH grade oil.
- The product is manufactured with the synthetic base oil and new additives. It gives excellent thermal stability 、viscosity retaining ability and seal compatibility. Its multi-grade viscosity of SAE 10W/40 is the best for highway and city driving mode.
- It is blended in new lower Phosphorus additives formulation which can offers motorcycle engine more wear reduction 、engine cleaning and engine life prolongation with catalyst converter.
- Package: (1) 1 liter bottle, 1 liter\*12 case.  
(2) 0.8 liter bottle, 0.8 liter\*12 case.
- The typical test results are as follow:

SAE Viscosity No.	10W/40
Sp., 15.6°C/15.6°C	0.8585
Viscosity Kin., cSt@40 °C, D445	93.4
@100 °C, D445	14.29
Viscosity Index, D2270	158
HTHS, cP (10 <sup>6</sup> s <sup>-1</sup> ), D5481	4.17
Flash Point, COC, °C, D92	224
Fire Point, COC, °C, D92	250
Acid Number, mg KOH/g, D664	1.7
Base Number, mg KOH/g, D2896	6.3
JASO Service Classification	MA
API Service Classification	SM
Product No.	LM51371

Note: Typical properties are based on standard tests under laboratory conditions. Variations that do not affect product performance are to be expected during normal manufacture. Please consult your local CPC representative if you have any questions.