



## MiRAGE PRO SN Synthetic Motor Oil 10W/40

- This Oil has meet the standard of API service grades SN by their specified testing institute.
- This Oil is an motor engine oil, not only suitable for the past motor engines which require SN grade oil but also the old model motors which need SM 、SL 、SJ grade oil.
- Manufactured with synthetic base oils, It gives excellent low temperature fluid stability 、viscosity retaining ability and well anti-oxidation. Its multi-grade viscosity of SAE 10W/40 is the best for all seasons in Asia and suitable for highway and city driving mode. The draining mileage is much longer than conventional mineral oils.
- It is blended in new formulation which can offers motor engine more wear reduction 、engine cleaning and engine life prolongation with catalyst converter and exhaust emission control system.
- Package: 1 liter bottle, 1 liter\*12 case.
- The typical test results are as follow:

|  |         |
|--|---------|
| SAE Viscosity No.                                  | 10W/40  |
| Sp. Gr., 15.6°C/15.6°C, D4052                      | 0.8541  |
| Viscosity Kin., cSt@40°C, D445                     | 95.60   |
| @100°C, D445                                       | 14.60   |
| Viscosity Index, D2270                             | 159     |
| HTHS, cP (10 <sup>6</sup> s <sup>-1</sup> ), D5481 | 3.9     |
| Flash Point, COC, °C, D92                          | 224     |
| Fire Point, COC, °C, D92                           | 250     |
| Acid Number, mg KOH/g, D664                        | 1.8     |
| Base Number, mg KOH/g, D2896                       | 7.0     |
| API Service Classification                         | SN      |
| Product No.  | LM51280 |

Note: Typical properties are based on standard tests under laboratory conditions. Variations that do not affect product performance are to be expected during normal manufacture. Please consult your local CPC representative if you have any questions.