



MiRAGE PRO SM 10W/40 Synthetic Motor Oil

- This Oil has been proved of API service grades SM by its specified testing institute.
- This Oil manufactured with synthetic base oils has excellent thermal stability 、 viscosity retaining ability and seal compatibility. Its multi-grade viscosity of SAE 10W/40 is the best for Asia and suitable for highway and city driving mode. The draining mileage is much longer than conventional mineral oils.
- It is blended in new lower phosphors formulation which can offers wear reduction 、 engine cleaning 、 gasoline saving and engine life prolongation.
- Package: 1 liter bottle, 1 liter*12 case.
- The typical test results are as follow:

SAE Viscosity No.	10W/40
Viscosity Kin., cSt@40°C, D445	91.8
@100°C, D445	14.29
Viscosity Index, D2270	158
HTHS, cP (10^6 s^{-1}), D5481	4.17
Flash Point, COC, °C, D92	224
Fire Point, COC, °C, D92	250
Acid Number, mg KOH/g, D664	1.70
Base Number, mg KOH/g, D2896	6.10
API Service Classification	SM
Product No.	LM51510

Note: Typical properties are based on standard tests under laboratory conditions. Variations that do not affect product performance are to be expected during normal manufacture. Please consult your local CPC representative if you have any questions.