

## MiRAGE PRO SN Fully Synthetic Motor Oil 5W/40

- This Oil has been proved of API service grades SN by its specified testing institute.
- This Oil manufactured with fully synthetic base oils has excellent thermal stability viscosity retaining ability and seal compatibility. Its multi-grade viscosity of SAE 5W/40 is the best for Asia and suitable for highway and city driving mode. The draining mileage is much longer than conventional mineral oils.
- It is blended in new lower phosphors formulation which can offers wear reduction engine cleaning gasoline saving and engine life prolongation.
- Package: 1 liter bottle, 1 liter\*12 case.
- The typical test results are as follow:

SAE Viscosity No.	5W/40
Sp. Gr., 15.6°C/15.6°C, D4052	0.8552
Viscosity Kin., cSt@40°C, D445	87.92
@100°C, D445	15.01
Viscosity Index, D2270	180
HTHS, $cP(10^6 s^{-1})$ , D5481	4.1
Flash Point, COC, °C, D92	222
Fire Point, COC, °C, D92	236
Acid Number, mg KOH/g, D664	1.75
Base Number, mg KOH/g, D2896	7.22
API Service Classification	SN
Product No.	LM51630

Note: Typical properties are based on standard tests under laboratory conditions. Variations that do not affect product performance are to be expected during normal manufacture. Please consult your local CPC representative if you have any questions.