

MIRAGE PRO SL SYNTHETIC MOTOR OIL 15W/50

- This Oil meets the API service grade SL by its specified testing institute.
- This Oils is an engine oil, not only suitable for the past gasoline engines which require SL grade oil but also the old model cars which need SH \ SG grade oil.
- Manufactured with high performance synthetic base oils, it gives excellent thermal stability viscosity retaining ability and seal compatibility. Its multi-grade viscosity of SAE 15W/50 is the best for Asia and suitable for highway and city driving mode.
- It is blended in new formulation which can offers wear reduction \(\cdot \) engine cleaning \(\cdot \) gasoline saving and engine life prolongation with catalyst converter.
- Package: 1 liter bottle, 1 liter*12 case.
- The typical test results are as follow:

SAE Viscosity No.	15W/50
Viscosity Kin., cSt@40°C, D445	128.2
@100°C, D445	17.54
Viscosity Index, D2270	151
Flash Point, COC, °C, D92	240
Fire Point, COC, °C, D92	265
Acid Number, mg KOH/g, D664	1.7
Base Number, mg KOH/g, D2896	6.1
API Service Classification	SL
Product No.	LM51402

Note: Typical properties are based on standard tests under laboratory conditions. Variations that do not affect product performance are to be expected during normal manufacture. Please consult your local CPC representative if you have any questions.