

MiRAGE PRO SL 15W/40 Super Motor Oil

- This Oil meet engine test standard of API service grade SL.
- This Oil is an motor engine oil, not only suitable for the past motor engines which require SL grade oil but also the old model motors which need SL · SJ grade oil.
- Manufactured with excellent base oils, It gives excellent thermal stability viscosity retaining ability and seal compatibility. Its multi-grade viscosity of SAE 15W/40 is the best for all seasons in Asia and suitable for highway and city driving mode.
- It is blended in new formulation which can offers motor engine more wear reduction engine cleaning and engine life prolongation with catalyst converter.
- Package: 1 liter bottle, 1 liter*12 case.
- The typical test results are as follow:

SAE Viscosity No.	15W/40
Sp. Gr., 15.6°C/15.6°C, D4052	0.886
Viscosity Kin., cSt@40°C, D445	109.8
@100°C, D445	14.26
Viscosity Index, D2270	132
HTHS, $cP(10^6 s^{-1})$, D5481	4.0
Flash Point, COC, °C, D92	240
Fire Point, COC, °C, D92	258
Acid Number, mg KOH/g, D664	1.63
Base Number, mg KOH/g, D2896	5.79
API Service Classification	SL
Product No.	LM51620

Note: Typical properties are based on standard tests under laboratory conditions. Variations that do not affect product performance are to be expected during normal manufacture. Please consult your local CPC representative if you have any questions.