

## MiRAGE PRO SN Synthetic Motor Oil 5W/30

- This Oil meets the standard of API service grade SN by its specified testing institute.
- This Oil manufactured with synthetic base oils has excellent thermal stability viscosity retaining ability and seal compatibility. Its multi-grade viscosity of SAE 5W/30 is the best for Asia and suitable for highway and city driving mode.
- It is blended in new lower phosphors formulation which can offers wear reduction engine cleaning saving and engine life prolongation.
- Package: 1 liter bottle, 1 liter\*12 case.
- The typical test results are as follow:

SAE Viscosity No.	5W/30
•	
Sp. Gr., 15.6°C/15.6°C, D4052	0.8672
Viscosity Kin., cSt@40℃, D445	63.23
@100°C,D445	10.51
Viscosity Index, D2270	156
HTHS, $cP(10^6 s^{-1})$ , D5481	3.2
Flash Point, COC, °C, D92	220
Fire Point, COC, °C, D92	242
Acid Number, mg KOH/g, D664	2.2
Base Number, mg KOH/g, D2896	7.7
API Service Classification	SN
Product No.	LM51281

Note: Typical properties are based on standard tests under laboratory conditions. Variations that do not affect product performance are to be expected during normal manufacture. Please consult your local CPC representative if you have any questions.